



MAXCLEAR® GRAFFITI CLEANER

PAINT REMOVING PRODUCT FOR THE ELIMINATION OF GRAFFITI

DESCRIPTION

High concentration and surfactant cleaner gel, formulated for the elimination of paint and graffiti.

USE

Elimination of graffiti over mineral substrates.

ADVANTAGES

- High penetrating power, being able to get through several layers of paint or coating.
- Does not contain acids or alkalis.
- Low evaporation index, increases its effectiveness preventing the paint from bonding again.
- Quick acting. Reduces the scraping, sanding, brushing with wire brush or shot blasting.
- Surfactant, easily dissolves paints.

APPLICATION

The application surface does not require any previous treatment. **MAXCLEAR® GRAFFITI CLEANER** is applied by brush, roller or spatula over the surface to be cleaned. A thick coat must be applied, both on horizontal and vertical surfaces.

After allowing the **MAXCLEAR® GRAFFITI CLEANER** to dry between 10 to 15 minutes, it is eliminated with spatula, water blasting or wire brush. In case the elimination of graffiti or paint has not been complete, the procedure can be repeated as many times as necessary.

After cleaning with **MAXCLEAR® GRAFFITI CLEANER**, it is advisable to coat and protect the surface with the anti-graffiti protection **MAXCLEAR® GRAFFITI**. Allow the surface to dry well and clean again.

After application clean the tools with abundant clean water.

COVERAGE

Approximately 3 m² per litre of product, or 2,6 m² per kg.

PACKAGING

25 kg drums and 5 kg cans.

STORAGE

MAXCLEAR® GRAFFITI CLEANER can be stored for one year in its original unopened containers, tightly closed.

SAFETY

- Avoid contact with the skin and eyes. Use appropriate clothing, rubber gloves and protective goggles and mask.
- Avoid inhaling (very toxic). Contains Methylene chloride.
- Keep away from fire and from the reach of children.
- In interior application provide adequate ventilation, using a mask when ventilation conditions are not satisfactory.
- Flammable.
- On hot days, separate from your face when opening the can.
- If it comes in contact with the skin, wash with abundant warm water and soap, in

case of contact with the eyes, wash thoroughly with water and get medical

assistance.

TECHNICAL DATA

Colour	Transparent off-white
Density (kg/l)	1,150 ± 0,05
Viscosity (mPa)	8,500 ± 2,500

GUARANTEE

The information contained in this leaflet is based on our experience and technical knowledge, obtained through laboratory testing and from bibliographic material. **DRIZORO[®], S.A.** reserves the right to introduce changes without prior notice. Any use of this data beyond the purposes expressly specified in the leaflet will not be the Company's responsibility unless authorised by us. We shall not accept responsibility exceeding the value of the purchased product. The data shown on consumptions, measurement and yields are for guidance only and based on our experience. These data are subject to variation due to the specific atmospheric and jobsite conditions so reasonable variations from the data may be experienced. In order to know the real data, a test on the jobsite must be done, and it will be carried out under the client responsibility. We shall not accept responsibility exceeding the value of the purchased product. For any other doubt, consult our Technical Department. This version of bulletin replaces the previous one.



DRIZORO, S.A.

C/ Primavera 50-52 Parque Industrial Las Monjas
28850 TORREJON DE ARDOZ – MADRID (SPAIN)
Tel. 91 676 66 76 - 91 677 61 75 Fax. 91 675 78 13
e-mail: info@drizoro.com Web site: drizoro.com

ISO 9001
ISO 14001

BUREAU VERITAS
Certification



n° 6003176 / 6003176-MA